

HOGEN[®] S Series Hydrogen Generation Systems



	S10	S20	S40
DESCRIPTION	On-site hydrogen generator in an integrated, automated, site-ready enclosure. Load Following operation automatically adjusts output to match demand.		
ELECTROLYTE	Proton Exchange Membrane (PEM) - caustic-free		
HYDROGEN PRODUCTION			
Net Production Rate: Nm ³ /hr @ 0°C, 1 bar SCF/hr @ 70°F, 1 atm SLPM @ 70°F, 1 atm kg per 24 hours	0.265 Nm ³ /hr 10 SCF/hr 4.7 SLPM 0.57 kg/24hr	0.53 Nm ³ /hr 20 SCF/hr 9.4 SLPM 1.14 kg/24hr	1.05Nm ³ /hr 40 SCF/hr 18.8 SLPM 2.27 kg/24hr
Delivery Pressure - Nominal	13.8 barg (200 PSIG)		
Power Consumed per Volume of H ₂ Gas Produced	6.7 kWh / Nm ³ 17.6 kWh / 100 ft ³		
Purity (Concentration of Impurities)	99.9995% (Water Vapor < 5 PPM, -65°C (-85°F) Dewpoint, N ₂ < 2 PPM, O ₂ < 1 PPM, All Other Undetectable)		
Turndown Range	0 to 100% net product delivery		
Upgradeability	N/A		
DI WATER REQUIREMENT			
Rate at Max Consumption Rate	0.235 L/hr (0.065 gal/hr)	0.47 L/hr (0.13 gal/hr)	0.94 L/hr (0.25 gal/hr)
Temperature	5°C to 35°C (41°F to 95°F)		
Pressure	1.5 to 4 barg (21.8 to 58.0 PSIG)		
Input Water Quality	ASTM Type II Deionized Water required, < 1 micro Siemen/cm (>1 megOhm-cm) ASTM Type I Deionized Water preferred, < 0.1 micro Siemen/cm (> 10 megOhm-cm)		

	S10	S20	S40
HEAT LOAD AND COOLANT REQUIREMENT			
Cooling	Air-Cooled; Ambient Air, 5°C to 40°C (41°F to 104°F)		
Max. Heat Load from System	1.1 kW / 3,754 BTU/hr	2.2 kW / 7,507 BTU/hr	4.3 kW / 14,673 BTU/hr
ELECTRICAL SPECIFICATIONS			
Recommended Breaker Rating	4 kVA	8 kVA	12 kVA
Electrical Specification	205 to 240 VAC, single phase, 50 or 60 Hz		
INTERFACE CONNECTIONS *Consult Installation Manual for details*			
H ₂ Product Port	1/4" CPI™ compression tube fitting, SS		
H ₂ / H ₂ O Vent Port	1/2" CPI™ compression tube fitting, SS		
DI Water Port	1/4" tube push-to-lock, polypropylene		
Calibration-Gas Port	N/A		
Coolant Supply Port	N/A		
Coolant Return Port	N/A		
Drain Port	1/4" tube push-to-lock polypropylene		
Electrical	Connect to on-board circuit breaker		
Communications	RS 232, Ethernet		
CONTROL SYSTEMS			
Standard Features	Fully automated, push button start/stop. E-stop. On-board H ₂ Leak detection. Automatic fault detection and system depressurization.		
Remote Alarm	Form C relay 2A/30VDC rated switching		
Remote Shutdown	Circuit breaker shunt trip		
ENCLOSURE CHARACTERISTICS			
Dimensions, W x D x H (Product / Est. Shipping)	31" x 38" x 42" (79 x 97 x 107 cm) / 38" x 45" x 52" (97 x 114 x 132 cm)		
Weight (Product / Est. Shipping)	475 lbs (216 kg) / 650 lbs (295 kg)		
Rating	IP22		
ENVIRONMENTAL CONSIDERATIONS *Do Not Freeze*			
Standard Siting Location	Indoor, level ± 1°, 0 to 90% RH non-condensing, Non-hazardous/non-classified environment		
Storage/Transport Temperature	5°C to 60°C (41°F to 140°F)		
Ambient Temperature Range	5°C to 40°C (41°F to 104°F)		
Altitude Range - Sea Level to:	1520 m (5000 ft)		
Ventilation	Proper ventilation must be provided from a non-hazardous area, at a rate in accordance with IEC60079-10, Zone 2 NE		
SAFETY AND REGULATORY CONFORMITY			
Maximum On-board H ₂ Inventory at Full Production	0.016 Nm ³ / 0.6 SCF / 0.0014 kg		
Cabinet Ventilation with Environment	NFPA 69 and EN 1127-1, Clause 6.2. Vent fan draws fresh air up to 28 Nm ³ /min (1000 ft ³ /min)		
Noise dB(A) at 1 Meter	< 70		
Approvals	cTUVus (UL and CSA equivalent), CE (PED, ATEX, LVD, Mach. Dir. EMC), NYFD Approval		

OPTIONS

Proton Onsite offers a wide range of options to tailor your HOGEN hydrogen generation system to meet your specific operational requirements. Please contact your local representative to discuss the current list of options available to best fit your needs.

Consult Proton Onsite Applications Department for proper installation guidelines. Specifications subject to change.



PD-0600-0061 Rev. C
 © 2011 Proton Energy Systems, Inc. All Rights Reserved.
 Proton, Proton OnSite, Proton Energy Systems, and HOGEN are trademarks of Proton Energy Systems, Inc. d/b/a Proton OnSite.

